

Marlow® DATASHEET

8 PLAIT PRE-STRETCH

Polyester option for windsurf downhauls and outhauls, grips well in cleats and provides good abrasion resistance.



CONSTRUCTION

MATERIAL CORE:	High Tenacity Polyester
MATERIAL COVER:	High Tenacity Polyester
CORE CONSTRUCTION:	Twisted
COVER CONSTRUCTION:	8 Plait Braided

PROPERTIES

BRAIDED CONSTRUCTION:	Flexible and easily knotted
HEAT SET:	Excellent stability improves 'feel'
PRE-STRETCHED:	Low initial elongation
HIGH STRENGTH:	Good general purpose line

PERFORMANCE

DIAMETER		CIRCUMFERENCE		MASS		AVERAGE STRENGTH			MIN STRENGTH		
mm	Inch	g/m	lb/100 ft	kg	lb	kN	kg	lb	kN		
4	5/32	13	0.92	428	944	4.20	330	728	3.24		
5	3/16	21	1.22	617	1360	6.05	530	1170	5.2		
6	7/32	29	1.68	891	1960	8.74	700	1540	6.87		
8	5/16	55	2.60	1410	3120	13.9	1230	2710	12.1		

Marlow Ropes Ltd
Ropemaker Park
Hailsham
East Sussex, BN27 3GU
England

Marlow Ropes, Inc.
Cordage Business Park
Plymouth
MA 02360
USA

www.marlowropes.com
UK: +44 (0) 1323 444 444
sales@marlowropes.com
US: +1 508 830 444
salesusa@marlowropes.com

Disclaimer

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied. Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.



Certification Number 315

ISO 9001