


Marlow® DATASHEET

DOUBLEBRAID


Our heat-set Doublebraid offers industry leading strength and stretch performance for a polyester braid-on-braid.

Easy splicing removes the need for bulky knots which also reduce a ropes strength.

Also good for high load applications thanks to the heat-setting process helping to reduce stretch and increase strength. A great versatile rope.



DIAMETER		CIRCUMFERENCE		MASS		AVERAGE STRENGTH			MIN STRENGTH		
mm	Inch	g/m	lb/100 ft	kg	lb	kN	kg	lb	kN		
6	7/32	28.4	1.90	1390	3060	13.6	1280	2820	12.5		
8	5/16	48	3.22	2560	5640	25.1	2360	5190	23.1		
10	3/8	74.7	5.01	3690	8140	36.2	3390	7480	33.3		
11	7/16	88.7	5.95	4370	9630	42.9	3930	8670	38.6		
12	11/2	111	7.44	4760	10500	46.7	4380	9650	43.0		
14	9/16	156	10.4	6050	13300	59.4	5570	12300	54.6		



Key Specifications:

Material:	High Tenacity Polyester
Construction:	Braid-on-braid
Core Construction:	12 strand braided
Cover Construction:	24 plait braided

Ropes designed in accordance with ISO 10325:201
Linear MBL refers to unspliced ropes determined in accordance with ISO2307:2019



Certification Number 315
ISO 9001

www.marlowropes.com

UK: +44 (0) 1323 444 444
sales@marlowropes.com

US: +1 508 830 0444
salesusa@marlowropes.com