

# Marlow<sup>®</sup> DATASHEET

## POLYESTER TOW ROPES

Strong, lightweight and flexible with excellent UV resistance, Marlow's 8 Strand Polyester Tow Ropes are ideally suited for small to medium sized armoured vehicles.



### CONSTRUCTION

**CONSTRUCTION:**  
**COLOURS:**

8 strand high tenacity polyester  
White, olive drab, desert sand

### TERMINATIONS:

250mm protected soft eye splice each end

### PERFORMANCE

GROSS VEHICLE WEIGHT	ROPE DIAMETER	ASSEMBLY LENGTH	ASSEMBLY WEIGHT	MINIMUM BREAK LOAD	COLOUR	MARLOW PART NUMBER	NSN
tonnes	mm	m	kg	kg			
-	28	4	4.46	16,000	white	WHA041	-
0.0 - 5.5	32	2.5	3.89	20,900	olive drab	WJG000	2540-99-820-5399
0.0 - 5.5	32	4	6.22	20,900	olive drab	WHA040	2540-99-823-2577
-	40	8	10.00	34,500	white	WHA075	-

Marlow Ropes Ltd  
Ropemaker Park  
Hailsham  
East Sussex, BN27 3GU  
England

Marlow Ropes, Inc.  
Cordage Business Park  
Plymouth  
MA 02360  
USA

www.marlowropes.com  
UK: +44 (0) 1323 444 444  
sales@marlowropes.com  
US: +1 508 830 444  
salesusa@marlowropes.com

#### Disclaimer

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied.

Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose.

Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines.

Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.



Certification Number 315

ISO 9001