

Marlow® DATASHEET

RAPTOR BULL ROPES

Braid on braid construction, easily spliced. ArmourCoated for 30% improvement in abrasion resistance. ArmourCoat reduces water absorption. Raptor Bull Ropes supplied with spliced stainless steel thimble.



APPLICATIONS:	Lowering line
MATERIAL	
CORE:	12 strand braided Polyester
COVER:	Braided 24 plait Polyester
CONSTRUCTION	
PROPERTIES:	High tenacity polyester with a hard wearing abrasion resistant ArmourCoat cover High strength and low stretch Supplied pre-spliced
LENGTHS:	Available in longer 100 or 200m lengths
COVER COATING:	ArmourCoat
TERMINATIONS	Spliced stainless steel thimble

PERFORMANCE

DIAMETER	LENGTH	COLOUR	WEIGHT		MINIMUM BREAK LOAD
mm	m		kg	g/m	kg
12	50	blue	5.6	111.0	3940
14	50	green	7.8	156.0	5010
16	50	red	9.7	193.0	5990
18	50	yellow	11.6	232.0	6550

Marlow Ropes Ltd
Ropemaker Park
Hailsham
East Sussex, BN27 3GU
England

Marlow Ropes, Inc.
Cordage Business Park
Plymouth
MA 02360
USA

www.marlowropes.com
UK: +44 (0) 1323 444 444
sales@marlowropes.com
US: +1 508 830 444
salesusa@marlowropes.com

Disclaimer

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied.
Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose.
Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines.
Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.
MA-DA-095 | ISSUE NO.2



Certification Number 315
ISO 9001