

## **VIPER2 SLING**

A factory sewn CE certified eye-to-eye sling made using a high strength cord incorporating the proven Viper Vectran cover. Viper2 slings have short stitching for efficient technique.

ALLES .

	THE REAL PROPERTY OF THE PROPE
	CLEAN REALESS
APPLICATIONS:	Prussik
MATERIAL COVER: CORE:	Vectran / Polyester 12 strand Vectran
CONSTRUCTION TEST STANDARDS: PROPERTIES: COLOURS:	UKCA and CE EN 566 High strength termination conforms to CE EN 566 Purple / natural
TERMINATIONS	Sewn eyes Serial numbered, factory CNC sewn terminations for regulatory compliance

## PERFORMANCE

DIAMETER	LENGTH	WEIGHT	AVERAGE BREAK LOAD	MINIMUM BREAK LOAD
mm	cm	g	kN	kN
8	50	57.2	23.6	22
8	60	64.6	23.6	22
8	70	72	23.6	22
8	80	75.5	23.6	22
8	90	80.9	23.6	22
8	1M	86.2	23.6	22

Marlow Ropes Ltd Ropemaker Park Hailsham East Sussex, BN27 3GU England

www.marlowropes.com UK: +44 (0) 1323 444 444 sales@marlowropes.com US: +1 508 830 444 salesusa@marlowropes.com



STAN

## Disclaimer

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied.

Marlow Ropes, Inc.

USA

Cordage Business Park Plymouth MA 02360

Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability

and fitness for a particular purpose. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice. MA-DA-085 | ISSUE NO.2

